

TABLE I.

FETRON	Tube	Idsr	gm	R _K	Side	Idsr	gm	R _K	Side	Comments	Socket
1005	407A	0.505 to 2.25	.35 Min.	240	2,3,4	3.0 to 11.0	1.8 to 6.0	240	6,7,8		S2
1008	407A	4.0 to 10.0	2.5 - 6.0	240	2,3,4	4.0 to 10.0	2.5 to 6.0	240	6,7,8		S2
1022	407A	2.0 to 6.0	2.5 Min.	240	2,3,4	2.0 to 6.0	2.5 Min.	240	6,7,8	Both sides cascoded	S2
1023	407A	.041 to 0.21	.4 Min.	240	2,3,4	.041 to 0.21	.4 Min.	240	2,3,4		S2
1024	407A	.4 to 2.0	.35 Min.	240	2,3,4	.4 to 2.0	.35 Min.	240	6,7,8		S2
1030	407A	3.0 to 10.0	2.2 - 6.0	240	2,3,4	2.0 to 5.5	1.5 Min.	240	6,7,8		S2
1032	407A	4.0 to 15.0	2.5 to 6.0	240	2,3,4	4.0 to 15.0	2.5 - 6.0	240	6,7,8		S2
1033	407A	3.6 to 7.3	3.5 Min.	240	2,3,4	3.5 - 11.0	2.0 Min.	240	6,7,8	2,3,4 = case	S2
1037	407A	0.45 to 1.37	.35 Min.	240	2,3,4	3.0 - 11.0	1.8 to 6.0	240	6,7,8		S2
1038	407A	3.0 to 11.0	1.8 to 6.0	240	2,3,4	.42 to 2.1	.35 Min.	240	6,7,8		S2
1042	407A	1.5 to 3.1	.35 Min.	"0"	2,3,4	3.0 to 11.0	1.8 to 6.0	240	6,7,8		S2
1044	407A	.41 to 2.0	0.3 to 1.0	240	2,3,4	.41 to 2.0	0.3 to 1.0	240	6,7,8		S2
1046	407A	4.0 to 15.0	2.5 to 6.0	240	2,3,4	4.0 to 15.0	2.5 to 6.0	240	6,7,8		S2
1077	407A	10 to 30	3.0 to 7.0	"0"	2,3,4	8 to 18.0	3.0 to 7.0	"0"	6,7,8	Regulator	S2

TABLE II.

FETRON	Tube	Idsr	gm	R _K	Comments	Socket
1000	408A	5.0 to 9.0	4.0 to 7.2	200	3 - 4 Sht.	S1
1001	408A	4 to 10	3.9 to 8.0	200		S1
1011	408A	4 to 10	3.5 to 7.5	200	Cathode diode 6AK5	S1
1013	408A	4 to 10	3.5 to 7.5	200		S1
1018	408A	7 to 12	3.9 to 8.0	200		S1
1029	408A	3 to 9	4.0 to 7.2	200		S1
1035	408A	5 to 9	4.0 to 7.2	200		S1
1036	408A	4 to 12	4.0 to 10.0	200		S1
1003	408A	2 to 5.5	2.5 to 7.0	200		S1
1012	408A	2 to 5.5	2.5 to 7.0	200		S1
1019	408A	2.0 Min.	3.5 Min.	200	Oscillator Also 2.5 to 6.0, 2.0 - 6.0, 200 Oscillator	S1
1049	408A	3.0 to 8.0	3.5 to 8.0	200		S1
1004	408A	.04 to 0.2	.35 Min.	200		S1
1039	408A	.4 to 1.8	.35 Min.	200		S1
1040	408A	1.5 to 5.5	2.0 to 8.0	200		S1
1014	408A	4 to 10	1.9 to 5.9	200	Has second gate on pin 7 Same as TR1014	S1
1056	408A	4 to 10	1.9 to 5.9	200		S1