

144, 430/440, 1200 MHz ALL MODE TRANSCEIVER



Direct Sampling Now Enters the VHF/UHF Arena

All mode, tri-band transceiver covering the 144, 430/440 as well as 1200 MHz

Real-time, high-speed spectrum scope for the 144, 430/440, 1200 MHz bands

New PA provides a powerful 100 W (144 MHz), 75 W (430/440 MHz) and 10 W (1200 MHz) output

Dualwatch operation and full-duplex operation in the satellite mode

Follows Icom's center display design style with a 4.3 inch touch screen color TFT LCD

D-STAR provides digital clear audio and Internet capable communication

Smooth satellite operation with normal/reverse tracking and 99 satellite channels

Digital Data (DD) mode provides 128 kbps data communication

IC-9700

GENERAL

Frequency coverage:	<USA version> 144.000–148.000, 430.000–450.000, 1240.000–1300.000 MHz
	<EUR version> 144.000–146.000, 430.000–440.000, 1240.000–1300.000 MHz
Mode:	SSB, CW, RTTY, AM, FM, DV, DD
Number of channels:	107 (99 Simplex + 6 Program scan edges + 2 CALL) × 3 bands, 99 (Satellite), 2000 (DR function)
Antenna connectors:	144 MHz SO-239 (50 Ω), 430/440, 1200 MHz Type-N (50 Ω)
Power supply requirement:	13.8 V DC ±15% (Negative ground)
Power consumption:	TX Less than 18 A (High power) RX 1.2 A typical (Standby), Less than 1.8 A (Maximum audio)
Operating temperature range:	–10 °C to +60 °C; 14 °F to 140 °F
Frequency stability:	Less than ±0.5 ppm (–10°C to +60°C; 14°F to 140°F)
Frequency resolution:	1 Hz
Dimensions:	240 × 94 × 238 mm, 9.4 × 3.7 × 9.4 in (W × H × D, projections not included)
Weight:	4.7 kg, 10.4 lb (approximate)

TRANSMITTER

Output power:	<SSB/CW/FM/RTTY/DV/DD> <AM>	
	144 MHz	0.5–100 W 0.125–25 W
	430/440 MHz	0.5–75 W 0.125–18.75 W
	1200 MHz	0.1–10 W 0.025–2.5 W
Modulation system:	SSB	Digital PSN modulation
	FM	Digital Reactance modulation
	AM	Digital Low Power modulation
	DV	Digital GMSK Reactance modulation
	DD	Digital Quadrature modulation
Spurious emissions:	<Harmonics>	<Out-of-band emission>
	144 MHz	Less than –63 dB
	430/440 MHz	Less than –61.8 dB
	1200 MHz	Less than –53 dB
Carrier suppression:	More than 50 dB	
Unwanted sideband:	More than 50 dB	
Microphone impedance:	600 Ω	

RECEIVER

Receiver system:	144, 430/440 MHz RF Direct Sampling
	1200 MHz Down Conversion IF Sampling
Intermediate frequency:	311–371 MHz (1200 MHz)
Sensitivity (Preamp: ON, Filter: SOFT):	
	SSB/CW (10 dB S/N) Less than 0.11 μV
	AM (10 dB S/N) Less than 1.0 μV
	FM (12 dB SINAD) Less than 0.18 μV
	DV (1% BER) (PN9) Less than 0.35 μV
	DD (1% BER) (PN9) Less than 1.59 μV
Selectivity (Filter: SHAPE):	
	SSB (BW=2.4 kHz) More than 2.4 kHz/–3 dB, Less than 3.6 kHz/–60 dB
	CW (BW=500 Hz) More than 500 Hz/–3 dB, Less than 700 Hz/–60 dB
	RTTY (BW=500 Hz) More than 500 Hz/–3 dB, Less than 700 Hz/–60 dB
	AM (BW=6 kHz) More than 6 kHz/–3 dB, Less than 15 kHz/–60 dB
	FM (BW=15 kHz) More than 12 kHz/–6 dB, Less than 20 kHz/–60 dB
	DV (12.5 kHz spacing) More than –50 dB
	DD (300 kHz spacing) More than –40 dB
Spurious and image rejection ratio:	
	SSB/CW 144, 430/440 MHz More than 70 dB, 1200 MHz More than 50 dB
	AM/FM/DV 144, 430/440 MHz More than 60 dB, 1200 MHz More than 50 dB
	DD 1200 MHz More than 50 dB
Audio output power:	More than 2.0 W (1 kHz, 10% distortion) into an 8 Ω load

OPTIONS



HM-219
Hand microphone with UP/DOWN switches (Same as supplied)



PS-126
DC power supply (13.8 V DC, 25 A maximum output)




RS-BA1 (Version 2)
IP remote control software



SM-50
Dynamic desktop microphone including [UP/DOWN] switches and a low cut function



SP-38
High quality audio and matching height Maximum input: 7 W



RS-MS1A
Remote control application for Android™. Download free from Google Play™.

- **MB-118** Mobile mounting bracket
- **MB-123** Carrying handle
- **OPC-2350LU** PC/Android™ data cable
- **SM-30** Compact, lightweight electret desktop microphone
- **SP-35** External speaker (2 m, 6.6 ft cable)
- **SP-41** External speaker with two input lines
- **CS-9700** Programming software

SUPPLIED ACCESSORIES

- HM-219, hand microphone
- DC power cable

REAR PANEL



- A** 144 MHz Antenna Connector
- B** 430/440 MHz Antenna Connector
- C** DC Power Socket
- D** 1200 MHz Antenna Connector
- E** LAN Port
- F** 10 MHz reference signal input
- G** Accessory Socket
- H** Data Jack
- I** USB/B Port
- J** CI-V Remote Control Jack
- K** KEY Jack
- L** External Speaker Jack MAIN
- M** External Speaker Jack SUB
- N** Ground Terminal

D-STAR (Digital Smart Technology for Amateur Radio) is a digital radio protocol developed by JARL (Japan Amateur Radio League). Icom, Icom Inc. and the Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. This product includes "zlib" and "libpng" open source software, and is licensed according to the open source software license. Android and Google Play are registered trademarks or trademarks of Google Inc. All other trademarks are the properties of their respective holders.

Icom Inc. 1-1-32, Kamiminami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

www.icom.co.jp/world

Count on us!

Icom America Inc.
www.icomamerica.com

Icom (Europe) GmbH
www.icomeurope.com

Icom (Australia) Pty. Ltd.
www.icom.net.au

Your local distributor/dealer:

Icom Canada
www.icomcanada.com

Icom Spain S.L.
www.icomspain.com

Shanghai Icom Ltd.
www.bjicom.com

Icom Brazil
E-mail: sales@icombrasil.com

Icom (UK) Ltd.
www.icomuk.co.uk

Icom France s.a.s.
www.icom-france.com