

**W2YMM Autopatch configuration for using voip.ms <https://voip.ms/>
This is for outbound autopatch calls only.**

@@

```
sip.conf
;
; SIP Configuration example for Asterisk
;
[general]
context=default ; Default context for incoming calls
allowoverlap=no ; Disable overlap dialing support. (Default is yes)
bindport=5060 ; UDP Port to bind to (SIP standard port is 5060)
bindaddr=0.0.0.0 ; IP address to bind to (0.0.0.0 binds to all)
srvlookup=yes ; Enable DNS SRV lookups on outbound calls
; Note: Asterisk only uses the first host
; in SRV records
; Disabling DNS SRV lookups disables the
; ability to place SIP calls based on domain
; names to some other SIP users on the Internet
```

```
register => 123456:PASSWORD123@newyork4.voip.ms:5060
```

```
[voipms]
canreinvite=no
context=voipms
host=newyork4.voip.ms
secret=PASSWORD123
type=peer
username=123456
disallow=all
allow=ulaw
allow=g729
fromuser=123456
trustpid=yes
sendrpid=yes
insecure=invite
nat=yes
```

@@

Note: Change the register line = to your credentials from voip.ms
Account and password

@@

**rpt.conf
Node Stanza**

```
context = voipms ; W2YMM AUTOPATCH PROVIDER
```

FUNCTION STANZA

```
; Autopatch up
;
6=autopatchup,context=voipms,noct=1,farenddisconnect=1,dialtime=20000 ;
```

