

<u>Referencia</u>	<u>Descripción</u>	<u>Unidades</u>	<u>Designación</u>
	PCB ZX-Uno VGA 2M	1	
	FPGA XC6SLX9-2TQG144C	1	U1
	SPI Flash Winbond W25Q128	1	U2
	IS61WV20488BLL-10TLI	1	U3
DM1AA-SF-PEJ	SD socket	1	J2
	6 pin molex connector 1.25mm	1	J9
MC001009	Micro USB socket	1	J1
	Oscilator 50MHz 5*7	1	U5
LD1117S33TR	Estabilizador de tensión 3,3V	1	U6
LD1117S12TR	Estabilizador de tensión 1,2V	1	U7
	3.5mm audio socket	2	J4, J5
	DB9 right angle male	2	J6
	DB15 high density RGB	1	J8
	PS/2 socket	1	J7
	Tira pin 2v+jumper	1	SW
	Tact switch 90º	3	RESET, S1, S2
1N4148WS-DIO	SMD Diode 1N4148, SOD-323	1	D1
	SMD 0805 LED GREEN	1	D5
	SMD 0805 LED RED	1	D4
	BC846 SOT-23 NPN Transistor	1	T1
	220 Ohm 0805 Resistor	2	R6, R7
	510 Ohm 0805 Resistor	8	R8, R9, R10, R11, R12, R13, R14, R15
	1K Ohm 0805 Resistor	3	R16, R17, R18
	2K Ohm 0805 Resistor	6	R19, R20, R21, R22, R23, R24
	10K Ohm 0805 Resistor	6	R27, R28, R29, R30, R31, R32
	10nF 0805 Capacitor	3	C2, C3, C4
	100nF 0805 Capacitor	9	C5, C9, C10, C11, C14, C15, C16, C26, C27
	4.7uF 0805 Capacitor	6	C28, C29, C30, C31, C34, C35
	Inductor 1k 0805	3	L1, L2, L3